



Product Overview

NDS3242 is a DEXIN's professional HD/SD audio & video encoder which has 2 channels of HDMI input (SDI module or YPbPr+HDMI+CVBS module optional) for MPEG-2 and MPEG-4 AVC/H.264 video encoding and MP2, MPEG 2-AAC, MPEG 4-AAC and AC3 audio encoding. It is also equipped with 1 ASI input for re-mux. The 2 encoded programs will output through 1 group of ASI ports or IP ports in 1 MPTS or 2 SPTS.

It adopts plug-gable design to make it conveniently change encoding module (HDMI/SDI/YPbPr+HDMI+ CVBS) as needed.

Key Features

- **MPEG2 & MPEG4 AVC/H.264 HD video encoding**
- **MP2, MPEG2-AAC, MPEG4-AAC and Dolby Digital AC3 audio encoding**
- **Support CC (closed caption), EIA 608, EIA 708 and Line 21 for SDI encoder board**
- **HDMI/SDI/YPbPr+HDMI+CVBS input module optional, pluggable and changeable encoding modules**
- **Support Low Delay function**

- Support PSI/SI editing and inserting
- Supports IP null packet filter
- ASI output (mirror out as 1 MPTS or 2 SPTS), IP (1 MPTS & 2 SPTS) output over UDP, RTP/RTSP
- LCD display, Remote control
- Web-based NMS management; Updates via web

Technical Specifications

| | | | |
|---|-------|--------------|--|
| <h3>HDMI Input</h3>  | Video | Input | HDMI*1 (with one for backup) |
| | | Encoding | MPEG2; MPEG4 AVC/H.264 |
| | | Bitrate | 1-19.5Mbps |
| | | Resolution | 1920*1080_60P, 1920*1080_50P, (-for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i |
| | | Low Delay | Normal, Mode 1, Mode 2, Manual |
| | | Chroma | 4:2:0 |
| | | Aspect Ratio | 16:9,4:3 |
| | Audio | Encoding | MPEG 2;MPEG 2-AAC; MPEG 4-AAC and Dolby Digital AC3 2.0 |
| | | Sample rate | 48KHz |
| | | Bitrate | 64/96/128/ 192/256/320kbps |

| | | | |
|--|-------|--------------|--|
| <h3>SDI Input</h3>  | Video | Encoding | MPEG2; MPEG4 AVC/H.264 |
| | | Input | SDI*1 |
| | | Bitrate | 1-19.5Mbps |
| | | Resolution | 1920*1080_60P, 1920*1080_50P, (-for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i |
| | | Low Delay | Normal, Mode 1, Mode 2, Manual |
| | | Chroma | 4:2:0 |
| | | Aspect Ratio | 16:9,4:3 |
| | Audio | Encoding | MPEG 2;MPEG2-AAC, MPEG4-AAC and Dolby Digital AC3 2.0 |
| | | Sample rate | 48KHz |
| | | Bitrate | 64/96/128/ 192/256/320kbps |

HDMI/YPbPr/CVBS

3-in-1 Input



| | | |
|---|---|--|
| <div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 10px;">Video (HDMI)</div> <div style="margin-bottom: 10px;">Audio (HDMI)</div> <div style="margin-bottom: 10px;">Video (YpbPr/CVBS)</div> <div>Audio (YpbPr/CVBS)</div> </div> | Encoding | MPEG2; MPEG4 AVC/H.264 |
| | Input | HDMI*1 |
| | Bitrate | 1-19.5Mbps |
| | Resolution | 1920*1080_60P, 1920*1080_50P, -for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i |
| | Low Delay | Normal, Mode 1, Mode 2, Manual |
| | Chroma | 4:2:0 |
| | Aspect Ratio | 16:9,4:3 |
| | Encoding | MPEG 2,MPEG2-AAC, MPEG4-AAC and Dolby Digital AC3 2.0 |
| | Input | HDMI*1 |
| | Sample rate | 48KHz |
| | Bitrate | 64/96/128/ 192/256/320kbps |
| | Encoding | MPEG2; MPEG4 AVC/H.264 |
| | Input | YPbPr*1 / CVBS *1 |
| | Bitrate | 1-19.5Mbps |
| Resolution | CVBS: 720x576_50i (PAL); 720x480_60i (NTSC) YpbPr: 1920*1080_60i, 1920*1080_50i; 1280*720_60p, 1280*720_50P | |
| Low Delay | Normal, Mode 1, Mode 2 | |
| Chroma | 4:2:0 | |
| Aspect Ratio | 16:9, 4:3 | |
| Encoding | MPEG 2; MPEG2-AAC; MPEG4-AAC and Dolby Digital AC3 2.0 | |
| Interface | 1*Stereo/2*mono | |
| Sample rate | 48KHz | |
| Bit rate | 64/96/128/ 192/256/320kbps | |

| | | |
|---|-------------------|---|
| <div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 10px;">System</div> <div>Physical Specification</div> </div> | Local interface | LCD + control buttons |
| | Remote management | Web NMS |
| | Stream In | 1 ASI in for re-multiplexing |
| | Stream Out | 2 ASI out (BNC type, same one TS, mirror as MPTS or SPTS) |
| | | IP (1 MPTS & 2 SPTS) over UDP, RTP/RTSP (RJ45, 1000M) |
| | DATA Port | 1000M |
| | NMS interface | RJ45, 100M |
| | Language | English |
| | Power supply | 100~240VAC, 50/60Hz |
| | Dimensions | 482*300*44mm |
| Operation temp | 0~45°C | |

Updated Date: 3rd Nov, 2022



All the specifications are subject to change without any further notice. All rights reserved.

Add: No. 10 & No. 12, Wuxing Fourth Road, Wuhou District, Chengdu 610045, Sichuan, P.R. China
 www.dsdivb.com/English Tel: +86-028-85558928 Fax: +86-028-85585255 Email: sunyu@dsdivb.com